HyperX Predator PCIe SSD

hyperxgaming.com

Ferocious performance for serious users.

HyperX® Predator PCle SSD offers large capacities and incredible speeds with both compressible and incompressible data to take your system to the edge. Faster than SATA-based SSDs, it's powered by a Marvell controller and delivers speeds up to 1400MB/s read and 1000MB/s write for ultra-responsive multitasking and an overall faster system, and it's available in 240GB–960GB capacities. It features a PCle Gen 2.0 x4 interface for high performance and an M.2 form factor to fit the next generation of desktops with an M.2 PCle slot. Its HHHL adapter comes with both standard and low-profile brackets and fits in slim profile desktop builds. HyperX Predator PCle SSD delivers top-of-the-line performance to match high-performance HyperX memory for consistent branding to keep you at the top of your game.

- > Highest performance speeds with large capacities
- > PCIe interface with multiple form factors
- > One-brand solution for top-of-the-line performance memory and SSD components



Features/specs on reverse >>



HyperX Predator PCIe SSD

FEATURES/BENEFITS

- > Fastest HyperX SSD Its Marvell controller delivers incredible sequential and random speeds, making Predator PCIe the fastest HyperX SSD.
- > Multiple capacities To suit your exact needs, HyperX Predator PCle SSD comes in capacities up to 960GB and can work as a boot drive or a true hard drive replacement.
- > Supports PCIe HyperX Predator PCIe SSD delivers blazing-fast PCIe Gen 2.0 x4 speeds that are much faster than any SATA-based SSD.
- > Ideal for desktop systems This SSD is available in an M.2 form factor with an optional HHHL adapter. Choose the option that best suits your build.

SPECIFICATIONS

- > Form factor M.2 2280
- > Interface PCle Gen 2.0 x4
- > Capacities¹ 240GB, 480GB, 960GB
- > NAND MLC
- > Controller Marvell 88SS9293
- > Baseline performance²

Compressible Data Transfer (ATTO)

240GB — 1400MB/s Read and 600MB/s Write 480GB — 1400MB/s Read and 1000MB/s Write

960GB - 1350MB/s Read and 1000MB/s Write

Incompressible Data Transfer (AS-SSD and CrystalDiskMark)

240GB — 1290MB/s Read and 600MB/s Write

480GB — 1100MB/s Read and 910MB/s Write

960GB - 1300MB/s Read and 1000MB/s Write

IOMETER Maximum 4k Read/Write

240GB — up to 160,000/ up to 119,000 IOPS 480GB — up to 130,000/ up to 118,000 IOPS 960GB — up to 160,000 / up to 126,000 IOPS

Random 4k Read/Write 240GB — up to 120,000/ up to 78,000 IOPS

480GB — up to 117,000/ up to 70,000 IOPS 960GB — up to 111,000 / up to 72,000 IOPS

PCMark® Vantage HDD Suite Score 240GB — 138,000

480GB — 139.000

960GB — 130,000 PCMark® 8 Storage Bandwidth 240GB — 331MB/s

480GB — 336MB/s

960GB — 414MB/s

PCMark® 8 Storage Score 240GB — 5,015

480GB - 5,017 960GB — 5.045

Anvil Total Score (Incompressible Workload)

240GB — 6,500 480GB — 6,700

960GB — 6,800

- > Power Consumption 1.38W Idle / 1.4W Avg / 1.99W (MAX) Read / 8.25W (MAX) Write
- > Storage temperature -40°C~85°C
- > Operating temperature 0°C~70°C
- > **Dimensions** 80mm x 22mm x 3.5mm (M.2)

180.98mm x 120.96mm x 21.59mm (with HHHL adapter – standard bracket) 181.29mm x 80.14mm x 23.40mm (with HHHL adapter – low-profile bracket)

> **Weight** 10g (M.2)

73g (with HHHL adapter – standard bracket) 68g (with HHHL adapter – low-profile bracket)

- > Vibration operating 2.17G Peak (7–800Hz)
- > Vibration non-operating 20G Peak (10–2000Hz)
- > Life expectancy 1 million hours MTBF
- > Warranty/support 3-year warranty with free technical support
- > Total Bytes Written (TBW)3

240GB - 415TB 1.6 DWPD

480GB - 882TB 1.7 DWPD4

960GB - 1600TB 1.8 DWPD4



PART NUMBERS

SHPM2280P2/240G

SHPM2280P2/480G

SHPM2280P2/960G

SHPM2280P2H/240G (with HHHL Adapter)

SHPM2280P2H/480G (with HHHL Adapter)

SHPM2280P2H/960G (with HHHL Adapter)

PACKAGE CONTENTS

M.2 only

- Hard drive cloning software – download coupon⁵

M.2 with HHHL Adapter

- Standard & low-profile brackets
- Hard drive cloning software download coupon⁵

4 Drive Writes Per Day (DWPD)





This SSD is designed for use in desktop and notebook computer workloads, and is not intended for Server

¹ Some of the listed capacity on a Flash storage device is used for formatting and other functions and is thus not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash Guide at kingston.com/flashguide.

² Based on "out-of-box performance" using a PCIe 3.0/2.0 motherboard. Speed may vary due to host hardware, software, and usage. IOMETER Random 4k Random Read/Write is based on 8GB partition.

³ Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A).