

G814JIR-N6002 - Model Specification

Uploaded On: 2023-11-24 10:02:03

FULL DETAIL

Part No	90NR0ID6-M003C0
Model Name	G814JIR-N6002
TTV	2023-11-27
End of Production	2024-12-31
EAN Code	4711387431511
UPC Code	197105431515
WEEE	3.333
BASE UNIT	VSNR0ID6-BU2110
Marketing Name	ROG Strix G18
Color	Eclipse Gray
Dimension (W x D x H)	39.9 x 29.4 x 2.31 ~ 3.08 cm (15.71in x 11.57in x 0.91in ~ 1.21in)
Weight	3.00 Kg (6.61 lbs)
Processor	Intel Raptor Lake i9-14***HX-T6K(8P+16e)
Chipset	Mobile Intel HM770 Express Chipsets
Discrete/Optimus	MUX Switch + NVIDIA Advanced Optimus
Graphic	NVIDIA GeForce RTX 4070 Laptop GPU
Graphic Wattage	ROG Boost: 2225MHz* at 140W (2175MHz Boost Clock+50MHz OC, 115W+25W Dynamic Boost)
Graphic Memory	8GB GDDR6
IGPU	Intel UHD Graphics
Panel Size	18-inch
Resolution	QHD+ 16:10 (2560 x 1600, WQXGA)
Refresh Rate	240Hz
Response Time (G2G)	3ms
Viewing Angle	85/85/85/85
Panel Tech	IPS-level
Brightness	500nits
Contrast	1000:1
DCI-P3 %	100.00%
Anti glare	Anti-glare display
Adaptive-Sync technology	G-Sync
Pantone	Pantone Validated
Nebula Display	ROG Nebula Display
Support Dolby Vision HDR	Yes
DIMM Memory	16GB DDR5-5600 SO-DIMM, the memory speed of the systems vary by CPU SPEC *2
Total System Memory	DDR5 32GB
Memory Slot	2x SO-DIMM slots
Memory Max.	32GB
Multi-channel memory technology	Support dual channel memory
System Storage Installed	1TB PCIe 4.0 NVMe M.2 SSD
M.2 slots support either SATA or N 2	
M.2 SSD Support List	512GB/1TB/2TB G4x4 PCIe SSD
Expansion Slot (includes used)	2x DDR4 SO-DIMM slots 2x PCIe
LAN	10/100/1000 Mbps

Wi-Fi/Bluetooth	Wi-Fi 6E(802.11ax) (Triple band) 2*2 + Bluetooth 5.3 Wireless Card (*Bluetooth version may change with BIOS update)
I/O Ports	1x RJ45 LAN port 1x Thunderbolt 4 support DisplayPort 1x USB 3.2 Gen 2 Type-C support DisplayPort / power delivery / G-SYNC 2x USB 3.2 Gen 2 Type-A
Display output	1x HDMI 2.1 FRL
Audio	1x 3.5mm Combo Audio Jack
Webcam	720P HD camera
Mic	Built-in array microphone
Keyboard Type	Backlit Chiclet Keyboard Per-Key RGB
Aura Sync	Yes
Speakers	2-speaker system with Smart Amplifier Technology
Audio Tech	AI noise-canceling technology Dolby Atmos Hi-Res certification Smart Amp Technology
Operating System	No preinstalled OS
Security	BIOS Administrator Password and User Password Protection Trusted Platform Module (Firmware TPM)
Battery	90WHrs, 4S1P, 4-cell Li-ion
Fast charging	Recharge from 0-50% in 30 minutes
Power	6.0, 280W AC Adapter, Output: 20V DC, 14A, 280W, Input: 100~240C AC 50/60Hz universal
Ecolabels & Compliances	ENERGY STAR