
UniFi® Protect







Camera G3 Flex

Stylish Full HD (1080p) mini turret camera with infrared LEDs and versatile mounting options for indoor and outdoor installations.



UniFi Protect G3 Flex camera is a Day/Night security camera that features a crisp 1080p video with IR capability. The flexibility of the mount allows putting the camera anywhere, like on-table, on the indoor wall, on the outdoor wall, on the pole, even put them in or on the ceiling.

Mechanical

Dimensions	Ø48 x 108 mm (Ø1.89 x 5.51")
Weight	170 g (6 oz)
Enclosure material	Polycarbonate
Mounting material	Polycarbonate
Weatherproofing	IPX4

Optics

Sensor	2MP HDR sensor
Lens	EFL 4 mm, f/2.0
View angle	Lens correction off: H: 87°, V: 47°, D: 104° Lens correction on: H: 80°, V: 46°, D: 92°
Night mode	Built-in IR LED illumination and IR Cut filter

Video

Video compression	H.264
Resolution	1920 x 1080 (16:9)
Maximum frame rate	25 FPS
Image settings	Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz

System

Management interface	UniFi Protect
Networking interface	10/100 MbE RJ45 port
Max. power consumption	4W
Power method	802.3af PoE mode A
Supported voltage range	24 to 48VDC
Button	Factory reset
Mounting	Flat table/wall, pole mount (kit included) Ceiling, pendant, professional wall mount (optional)
Operating temperature	-20 to 40° C (-4 to 104° F)
Operating humidity	20 to 90% noncondensing
Certifications	FCC, IC, CE



Audio

Microphone Yes (can be disabled in software)

Software

Controller software	UniFi Protect
Mobile apps	UniFi Protect iOS and Android

