

TESLA TT34X81-1232IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Turbo Function, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Honeycomb filter, Washable Filter, Ionizer filter, Wi-Fi Included, I FEEL function

Capacity				12000BTU
Rated volt and frequency			V/Hz	220-240V~/50HZ
Mode				CoolingHeating
Rated capacity			W	11600 (1000~3770)11670 (1000~3810)
Power input			W	1130922
Current input			A	5.804.70
SEER-SCOP/ Energy Class			W/W	6,1/ A++4,0/A+
Operating range (°C)				0 - 53°C-20°C - 30°C
Dehumidifying			Kg/h	1.2
Degree of protection (IN) / (OUT)			(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)			Class I / Class II	I/I
Max. input consumption			W	1720
Max. current			A	10
Compressor		Model		KSN98D32UEZ
		Type		Rotary
		Brand		GMCC
Indoor	Fan motor	Model		1170030067G
		Power input	W	20W output
		Capacity	uF	2
		Indoor Fan Speed RPM	r/min	≤1320
	Indoor fan	Dia. / Length	mm	Φ92×578
	Indoor Air Circulation (m³/h)		m³/h	550/550
	Indoor Noise Level dB		dB(A)	22/25/33/37/40
	Net Dimension (L×W×H)		mm	777×250×201
	Packing Dimension (L×W×H)		mm	850×320×275
	Net Weight/Gross Weight		Kg	8/10.5
Outdoor	Fan motor	Model		1170040162AB
		Power input	W	33W output
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	≤1000
	Outdoor fan	Length	mm	φ384×134
	Outdoor Noise Level dB		dB(A)	29/33/39/46/50
	Net Dimension (L×W×H)		mm	777×498×290
	Packing Dimension (L×W×H)		mm	818×520×325
	Net Weight/Gross Weight		Kg	22/25
	Refrigerant type/weight		g	R32/550g/675
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
Refrigerant piping		Liquid side / Gas side	mm	6.35/9.52
		Max. refrigerant pipe length / Max. difference in level	m	25/10