

TESLA TA53FFLL-1832IAW



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Wi-Fi included, I FEEL function

Capacity				18000BTU	
Rated volt and frequency			V/Hz	220-240V~/50HZ	
Mode				CoolingHeating	
Rated capacity			W	5250 (1200~5400)5500 (1200~5800)	
Power input			W	16601490	
Current input			A	7.356.60	
SEER-SCOP/ Energy Class			W/W	6,57/ A++4,02/A+	
Operating range (°C)				14 - 43°C-15 - 30°C	
Dehumidifying			Kg/h	1.8	
Degree of protection (IN) / (OUT)			(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)			Class I / Class II	I/I	
Max. input consumption			W	2900	
Max. current			A	12	
Compressor		Model		KSM135D23UFZ	
		Type		DC	
		Brand		GMCC	
Indoor	Fan motor	Model		D-310-30-8	
		Power input	W	30	
		Capacity	uF	1,5	
		Indoor Fan Speed RPM	r/min	1180	
	Indoor fan	Dia. / Length	mm	Φ106x715	
	Indoor Air Circulation (m³/h)		m³/h	850	
	Indoor Noise Level dB		dB(A)	47	
	Net Dimension (L×W×H)		mm	900×310×225	
	Packing Dimension (L×W×H)		mm	970×382×302	
	Net Weight/Gross Weight		Kg	12,0/14	
	Outdoor	Fan motor	Model		D-40-8
			Power input	W	40
Capacity			uF	1,5	
Outdoor Fan Speed RPM			r/min	900	
Outdoor fan		Length	mm	421	
Outdoor Noise Level dB		dB(A)	58		
Net Dimension (L×W×H)		mm	800×545×315		
Packing Dimension (L×W×H)		mm	920×620×400		
Net Weight/Gross Weight		Kg	35,0/37,5		
Refrigerant type/weight		g	R32/1280		
Max. Discharge/Max. Suction pressure		Mpa	4,28/1,18		
Refrigerant piping		Liquid side / Gas side	mm	6.35 (1/4)/12.7 (1/2)	
		Max. refrigerant pipe length / Max. difference in level	m	25/10	