

TESLA TA27FFLL-09410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

Capacity			9000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	2700 2800	
Power input		W	841 776	
Current input		A	3.66 3.37	
EER-COP		W/W	3.21 3.61	
Energy Class			A A	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	8.5	
Max. current		A	1600	
Compressor		Model	ASN89V1UDZ	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK12-4B	
		Power input	W	12
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1150
	Indoor fan	Dia. / Length	mm	Ø92 / 500
	Indoor Air Circulation (m³/h)		m³/h	450
	Indoor Noise Level dB		dB(A)	33/30/27/24
	Net Dimension (LxWxH)		mm	700x285x188
	Packing Dimension (LxWxH)		mm	770x355x272
	Net Weight/Gross Weight		Kg	6,5/8,15
Outdoor	Fan motor	Model	YDK25-6	
		Power input	W	25
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	820
	Outdoor fan	Dia. / Length	mm	Ø327 / 132
	Outdoor Noise Level dB		dB(A)	50
	Net Dimension (LxWxH)		mm	660x500x240
	Packing Dimension (LxWxH)		mm	780x570x345
	Net Weight/Gross Weight		Kg	21.5/24,65
	Refrigerant type/weight		g	R410/640
Design pressure (Hi/Low)		Mpa	4.15/1.15	
Refrigerant piping	Liquid side / Gas side		mm	Ø6.35(0,5) / Ø9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level		m	18/6