

TESLA TA33FFLL-12410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	3300 3450	
Power input		W	1028 955	
Current input		A	4.47 4.15	
EER-COP		W/W	3.21 3.61	
Energy Class			A A	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	8.5	
Max. current		A	1750	
Compressor		Model	ASM125V1VFT	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK18-4B	
		Power input	W	18
		Capacity	uF	1.5
		Indoor Fan Speed RPM	r/min	1330
	Indoor fan	Dia. / Length	mm	Ø97.8 / 558
	Indoor Air Circulation (m³/h)		m³/h	560
	Indoor Noise Level dB		dB(A)	36/33/30/27
	Net Dimension (LxWxH)		mm	800x300x197
	Packing Dimension (LxWxH)		mm	870x370x282
Net Weight/Gross Weight		Kg	8/10,8	
Outdoor	Fan motor	Model	YDK25-6	
		Power input	W	25
		Capacity	uF	1.5
		Outdoor Fan Speed RPM	r/min	820
	Outdoor fan	Dia. / Length	mm	Ø390 / 140
	Outdoor Noise Level dB		dB(A)	52
	Net Dimension (LxWxH)		mm	660x500x240
	Packing Dimension (LxWxH)		mm	780x570x345
	Net Weight/Gross Weight		Kg	29/31,65
Refrigerant type/weight		g	R410/660	
Design pressure (Hi/Low)		Mpa		
Refrigerant piping	Liquid side / Gas side		mm	Ø6.35(0,5) / Ø9.52(0,6)
	Max. refrigerant pipe length / Max. difference in level		m	18/6