

TESLA TA70FFLL-24410A



FEATURES

Anti-Fungus function, Self-Cleaning, Self-diagnosis Function, Super EMC performance, Anti-Rust Cabinet, Intelligent defrosting, Super Quiet design, Backup Switch, Turbo Operation, Hydrophilic Aluminium Fin, Sleep Mode, Fault Code indication, Low Noise Airflow System, Dual Sides Water Outlet, Multiple Fan Speed, Auto-Restart, Timer, Air blade, Washable Filter, Anti-Cold-Air (Heat Pump Only), Ionizer, I FEEL function

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	7000 7200	
Power input		W	2325 2243	
Current input		A	10.1 9.75	
EER-COP		W/W	3.01 3.21	
Energy Class			A A	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2900	
Max. current		A	16.5	
Compressor		Model	ASG240V1VMU	
		Type (Rotary/Piston/scroll)	ROTARY	
		Brand	GMCC	
Indoor	Fan motor	Model	YYK25-4D	
		Power input	W	25
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	1230
	Indoor fan	Dia. / Length	mm	Ø107.9 / 661
	Indoor Air Circulation (m³/h)		m³/h	1050
	Indoor Noise Level dB		dB(A)	40/37/34/31
	Net Dimension (LxWxH)		mm	970x315x235
	Packing Dimension (LxWxH)		mm	1047x385x317
	Net Weight/Gross Weight		Kg	11.5/14,3
Outdoor	Fan motor	Model	YDK69-6A	
		Power input	W	69
		Capacity	uF	4
		Outdoor Fan Speed RPM	r/min	830
	Outdoor fan	Dia. / Length	mm	Ø470 / 140
	Outdoor Noise Level dB		dB(A)	55
	Net Dimension (LxWxH)		mm	825x655x310
	Packing Dimension (LxWxH)		mm	945x725x435
	Net Weight/Gross Weight		Kg	46/50,2
	Refrigerant type/weight		g	R410/1500
Design pressure (Hi/Low)		Mpa	4.15/1.15	
Refrigerant piping	Liquid side / Gas side		mm	Ø6.35(0,5) / Ø15,88(0,75)
	Max. refrigerant pipe length / Max. difference in level		m	18/6