Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, Network Card, AVR, LCD

SMT1500RMI2UNC

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.	
Lead time	Usually in Stock	
Main		
Product or component type Uninterruptible power supply (UPS)		
Batteries & Runt	ime	
Run Time	View Runtime Graph 🖸	
Efficiency View Efficiency Graph		

Efficiency	View Efficiency Graph 🖾	
Battery type	Lead-acid battery	
Additional information	Configurable for 220 : 230 or 240 nominal output voltage	
Extended runtime	0	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	3 h	
Number of battery replacement quantity	1	
Battery life	35 year(s)	
Replacement battery	APCRBC159	
Battery charger power	144 W rated	

General

Provided equipment	CD with software Documentation CD Installation guide Rack mounting support rails Smart UPS signalling RS-232 cable Temperature probe USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Rates duty January 2016

Life Is On Schneider

Physical

-	
Number of rack unit	2U
Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	45.7 cm
Net weight	28.58 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

Input

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Input Connection Type	IEC 320 C14
Input voltage limits	151302 V adjustable 160286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

•	
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1000 W
rated power in VA	1500 VA
output connection type	4 IEC 320 C13 2 IEC Jumpers
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	1000 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications EAC RCM VDE UK PSTI

Environmental

Acoustic level	46 dBA
Heat dissipation	90 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.00000000015240.000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

control panel	Multifunction LCD status and control console	
Emergency power off	Optional	
Preinstalled device	Network management card 3 with environmental monitoring	
Control panel	LED status display with on line : on battery : replace battery and overload indicators	
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays	

Surge Protection and Filtering

Surge energy rate	459 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.1 cm
Package 1 Width	60.3 cm
Package 1 Length	59.4 cm
Package 1 Weight	31.84 kg

Contractual warranty

Warranty

 $\ensuremath{\textbf{3}}$ years repair or replace (excluding battery) and 2 years for battery

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

Q			
	Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1408	
	Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
REACh Regulation	REACh Declaration
U Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Product datasheet SMT1500RMI2UNC

Image of product / Alternate images

Alternative

