

NRT3-11000K
NETYS RT 11KVA 230VAC+BAT

Strong points

- Simple to install
- High protection and availability
- Certified performance
- Easy to use
- Extended and flexible back-up time

General characteristics

- Rail kit.
- Embedded dry-contact interface (5000-11000 VA).
- Input mains switch breaker (5000-11000 VA).
- Connection for battery extension modules.
- Port for parallel operation (5000-11000 VA).
- Power off the UPS remotely.
- Internal temperature sensor.

Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

Link to the reference

Complete and professional, NETYS RT is a single-phase rack-tower UPS ensuring protection and availability of IT infrastructure that meet both requirements of power reliability and installation flexibility.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	NeTYS RT 11000VA/10000W VFI UPS 1/1 WITH BATTERY INTEGRATED +RAILS
Effective date	2021-04-01
Country of origin	IT
Weight	84

ETIM - Electrical characteristics

Input voltage [V]	175..280
Primary frequency [Hz]	40..70
Number of phases primary	1
Output voltage [V]	200..240
Secondary frequency [Hz]	50..60
Output effective power [W]	10000
Output apparent power [VA]	11000
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Max. voltage distortion output (linear load) [%]	2
Output power factor	0.91

ETIM - Mechanical characteristics

Height [mm]	220
Width [mm]	440
Depth [mm]	650
Weight [kg]	84
Construction type	482.6 mm (19 inch) device
Input connection	Fixed connection
Number of output connections fixed connection	1

ETIM - Technical features

USB interface	Yes
Bridging time full load [min]	6.3
Suitable for network-management	Yes
USV- technology	Online
Overall efficiency [%]	95.5
Efficiency in eco-mode [%]	98
Potential free switch contact	Yes
Auto shut down function	Yes

Logistics

GTIN/EAN	8027122754811
Customs number	8504409590

Norms

Conformity to standards	IEC
Technical Characteristics	
Depth	650
Height	220
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn	11
Pn	10
Conf	C1
Input voltage	230
Rate (min)	11
Rate (max)	11
Life Time	03-05
Typical Backup Time	9
Configuration	UPS Single Unit(s) with Bypass