

Eaton 9E3000IR

Catalog Number: 9E3000IR

Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs: (6) C13, (1) C19, Rack, 2U

General specifications



Product Name

Eaton 9E UPS

Catalog Number

9E3000IR

EAN

3553340710353

Product Length/Depth

608 mm

Product Height

86.5 mm

Product Width

438 mm

Product Weight

31.3 kg

Compliances

CE Marked

TUV

Certifications

IEC/EN 62040-1

IEC/EN 62040-2

CE

Battery

Battery type

Sealed, lead-acid

Runtime graph

\$row.attributeValue.cdata

Battery replacement

Replacable batteries

Battery quantity

6

Battery management

Temperature compensated
charging method
Automatic battery test
Deep discharge protection

Battery rating

12 V / 9 Ah

Extended battery capability

Yes

Electrical output

Receptacle

(6) C13 + (1) C19

Voltage

230V

Wattage

2700 W

Output power factor

0.9

Output voltage range

220/230/240 V +/- 2%

Output waveform

Sine wave

Output nominal voltage

230V default (220/230/240V)

Voltage distortion output (linear load) - max

3

Feed type

1

Topology

Online/Double-conversion

VA rating

3000 VA

Electrical input

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input power factor

>.99

Input cord length

1.8m

Communications

Includes network card

No

Communication

USB port (HID compliant)

Serial port (RS232)

Mini-terminal block for
remote power off

Ethernet interface

No

User interface

Multilingual LCD display

Input frequency range

40-70 Hz

Potential free switch contact

Yes

Expansion slots

One slot for optional communication card

Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

Type of interface

Other

Environmental

Altitude

3000 m

Noise level

<45 dB at 1 meter

Temperature range

0° to 40°C (32° to 104°F)

Relative humidity

0-96% non-condensing

Additional specifications

Construction type

482.6 mm (19 inch) device

Package contents

UPS

(2) IEC-IEC output cables

USB cable

Rack-mounting kit (rails and brackets)

Safety instructions

Quickstart guide

Phase (output)

1

Internal bypass

Yes

Auto shutdown function

Yes

Color

Black

Efficiency

91

Rack mounting kit

Yes

Phase (input)

1

Hot swap power

No

Resources

Declarations of conformity

[EU Declaration of Conformity](#)

Manuals and user guides

[Advanced user guide 9E Rack](#)

[9E Rack UPS quick start guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)